

Index



A

Accumulation, 53

Accuracy:

numerical integration, 83–84

sensor, 383, 772–773

Adaptive tuning:

expert system, 528

gain scheduling, 518, 529, 709, 715

input conversion, 519

reasons for, 512–517

relay auto-tuning, 527

selection of method, 529

valve characteristic, 520–525

Alarms, 795, 890

Aliasing:

antialiasing filter, 393

due to sampling, 362, 989

Amplitude:

amplitude ratio, 121–123, 316, 412,
988–989

response to sine, 121

(*See also* Frequency response)

Analog:

computation, 257

signals, 212–215, 358–359

Anti-reset windup, 399–402, 604–605,
715

Array (*see* Relative gain array)

Averaging filter, 394

Averaging level control, 563–564,
569–570

B

Bandwidth, 419

Benefits, control, 28–35, 423–425

Blending:

controllability, 627, 637

gasoline, 866

interaction, 632

loop pairing, 663

model, 621

operating window, 625

- Blending—*Cont.*
 optimum, 866–870
 tuning for, 646–648
- Block diagrams:
 algebra, 116, 118, 143, 244
 cascade, 463
 definition of, 115
 feed forward, 489
 multiloop, 630
 IMC, 592, 994
 reduction to transfer function, 116, 244
 series, 143
 single-loop, 243, 974
 Smith predictor, 600
- Bode:
 cascade, 468
 closed-loop, 412–415
 generalized plots, 323–326
 key aspects of plots, 328
 plot, 123
 stability criterion, 313–317
 limitations of, 316
- Boiler:
 control of, 27, 474
 efficiency of, 32–34
 optimization of, 861–865
 (*See also* Steam system)
- Bounded input-output stability, 304, 307–308
- ## C
- Cascade:
 block diagram, 463
 degrees of freedom, 460–461
 design criteria for, 461
 examples:
 chemical reactor, 471–473
 distillation, 690–691
 fired heater, 473
 heat exchanger, 458–460
 levels of, 473
 performance, 462–468
 primary variable, 460
 secondary variable, 460
 terminology, 460
 transfer functions, 462
 tuning, 469
- Cause-effect relationship, 6–7, 114, 651
- Centralized control, 617, 727
- Characteristic, valve:
 examples, 520–525
 inherent, 520
 specifying for linearizing loopgain, 524
- Characteristic equation:
 definition, 309, 630
 relation to stability, 309–310, 316, 643, 987
- Characteristic polynomial:
 definition of, 108, 932
 relation to stability, 109
 roots of, 109, 932
- Checklist, for design, 820–822
- Chemical reactor, packed bed:
 cascade, 471–473
 feedforward, 495–497
 inferential, 549–552
 variable structure, 713–714
- Chemical reactor, stirred tank, 62, 72, 84–86
 isothermal, 62, 72
 nonisothermal:
 cascade design, 475–476
 control design, 835
 control performance, 438–440
 linearized, 900
 model for, 85, 897–901
 multiple input-output, 163–165
 operating window, 781–783
 recycle, with, 785
 selecting variables, 216–218
 signal select, 710–712
 transfer function, 902
- series:
 block diagram, 944
 inverse response, 944–945
 model, 64–67, 943–944
 transfer function, 944
- stability, without control, 902–906
- steady-states:
 calculating, 902–904
 multiple, 905
 stabilizing via control, 905
- Combustion:
 benefits for, 32–34
 excess oxygen control, 27
 fuel control, 500–501
 (*See also* Fired heater)
- Complex numbers:
 magnitude, 122, 316–317, 936–937
 phase angle, 122, 316–317, 936–937
 polar form, 122, 316–317, 936–937

- Composition control:
 blending and mixing, 270, 282, 512–519, 646–648
 chemical reactor, 37, 216, 438, 475, 835
 flash, 23, 537–544, 768, 802–803
 (See also Distillation)
- Computation:
 analog, 257–258
 digital, 358–362
- Computer:
 analog, 257–258
 digital, 358–362
 control implementation, 365–367, 974, 983–989
 simulation, 82–84, 422–425
 (See also Digital control)
- Computer-aided calculations, 82–84, 421–422
- Conservation
 component, 53
 energy, 53, 898
 material, 53
- Constitutive relationships, 54
- Constraints, 26
 control, 715–720
 hard or soft, 767–770
 valve position control, 718–719
 (See also Operating window)
- Continual improvement, 859
- Continuous cycling, 342–343
- Continuous-flow stirred tank (CST):
 chemical reactor:
 heat-integrated, 785
 with recycle, 155–157
 (See also, Chemical reactor, stirred tank)
 heater, 76–80, 253–257, 458–461, 483–486
 mixer, 186–187, 223–225, 270, 512
- Continuous-time variables, 98, 212
- Control:
 algorithms:
 DMC, 735–748
 IMC, 590–600
 lead/lag, 485–486
 PID, 252
 Smith predictor, 600–603
 approaches, 228
 automated vs. manual, 228–231
 benefits, 28–35, 425
 definition, 6
 design, 216–218, 823, 834
 feedback, 6–7, 212, 243
- Control—*Cont.*
 feedforward, 488
 objectives, seven categories, 20–25, 768, 838
 (See also Model predictive control)
- Control design form, 768, 838
- Control objectives, 20, 216, 269, 768
- Control performance:
 best possible, 426–427, 490
 control system factors, 433–440
 economic analysis, (see Benefits, control)
 fraction dead time, 279, 426–429
 factors affecting, 444
 by frequency response, 412–415
 measures, 219–223, 240–241
 multivariable systems:
 disturbance type, 667, 677–679
 interaction, 616
 (See also Relative disturbance gain)
 process factors, 425–432
 robust, 268–269, 411
 by simulation, 422
- Control system:
 hierarchy, 829
 layout, 9–10, 212–213, 359–361
- Control valve:
 characteristic, 520
 dynamics, 776
 failure position, 777
 range, 776
 selection, 217
- Controlled variable:
 selection of, 7–8, 225, 536, 771–773, 775, 787, 840
- Controller:
 dimensionless gain, 397
 error, 242–243
 execution frequency, 370, 373
 flowchart, 403
 frequency response of, 325–326
 location, 9–10
 manipulated variable, 217
 measured variable, 216
 nonlinear, 517, 567
 performance (see Control performance)
 sense switch, 396–397
 tuning:
 Ciacone, 278–286
 comparison, 347
 dynamic matrix, 750
 fine, 289–293
 goals, 268–269

- Controller—*Cont.*
 tuning—*Cont.*
 IMC, 598
 Lopez, 287
 multiloop, 638–646
 robustness, 268–269, 338–341
 Ziegler-Nichols, 329–330, 347
- Corner frequency, 323
 Critical frequency, 315
 Crossover frequency, 315
 CST (*see* Continuous-flow stirred tank)
- D**
- Damping:
 coefficient, 138–139
 critically, 139
 overdamped, 139
 underdamped, 139
- Dead time:
 Bode plot, 324
 compensation, 600
 computer programming, 922
 definition, 103
 discrete, 977
 effect on performance, 426–427
 effect on stability, 334–337
 frequency response, 318
 Padé approximation, 913
- Decay ratio, 220
 Decentralized control, 616–617
- Decoupling:
 application criteria, 690
 designs:
 calculated controlled variables,
 685–686
 calculated manipulated variables,
 684–685
 explicit controller calculations,
 686–689
 performance, 689–690
 sensitivity to errors, 689–690
 (*See also* Interaction)
- Degrees of freedom:
 in control design, 217, 460–461, 708,
 711, 778
 effect of control, 254, 778
 in modelling, 54–55
- Derivative:
 approximation, 366
 definition of, 56
 filter, 402
- Derivative—*Cont.*
 Laplace transform of, 101
 mode:
 behavior, 249–252
 frequency response, 326
 noise transmission, 252, 292–293
 time, 250
 z-transform, 978
- Design, control:
 control design form (CDF), 768–769,
 838–839
 controllability, 780–781
 degrees of freedom, 778
 dynamics:
 disturbance, 444
 feedback, 444
 loop pairing, 695
 operating window, 624–626, 681, 781,
 788–789
 procedure, integrated, 834
 process decomposition, 831
 sequence of steps, 823
 temporal hierarchy, 825
- Detuning factor, 678
 Deviation variables, 71, 111
- Diagnostic:
 model, 183
 tuning, 290
- Difference equations:
 controllers, 367, 493, 595, 994–995
 discrete models:
 approximate, 923
 empirical, 188
 exact, 923, 986
- Differential equations:
 discrete form, 188, 923, 986
 linearization of, 70–72
 numerical solution:
 error control, 84
 Euler, 83, 423
 Runge-Kutta, 84
 solution by:
 integrating factor, 895
 Laplace transforms, 102
- Digital control:
 computing network, 359
 dynamic matrix control, 735
 internal model control, 595
 lead/lag, 493
 performance of PID, 367–369
 ringing, 370–371, 982, 992
 sampling:
 hold, types of, 364–366
 period selection, 369

- Digital control—*Cont.*
 sampling—*Cont.*
 simulation, 423
 tuning modifications for, 370
- Dimensional analysis, tuning, 278–286
- Direct-acting feedback, 396
- Distillation:
 cascade control, 690
 composition control of:
 inferential, 545–549
 interaction in, 637
 operating window, 625–626
 relative disturbance gain (RDG),
 679–680
 tuning for, 648
 decoupling control, 689
 dynamic matrix control of, 746–747,
 754–756
 feedforward control of, 500–501
 industrial case study, 949–960
 modelling of:
 empirical, 62, 622–623
 fundamental, 157–163
 regulatory control of:
 energy balance, 664
 material balance, 665
- Distributed control system:
 advantages of, 361
 structure of, 359
- Disturbance:
 causes, 7
 interaction effects (*see* Relative
 disturbance gain)
 models, 220, 224, 415, 444, 496, 666
 response, closed-loop:
 frequency response, 412–418
 simulation, 422–425
- Dominant variable, 779, 827
- Draining tank, 75–77, 106–107
- Drawings, 12–13
 instrument symbols, 889–892
 process equipment, 892–894
 valve symbols, 892
- Dynamic compensation, 551
- Dynamic matrix control (DMC):
 approximate inverse for, 729
 controller formulation, 737–738
 discrete step process model, 730–734
 feedback signal, 740–742
 future prediction, 735
 horizon, 737
 model, step-weight, 730
 move suppression, 743
- Dynamic matrix control (DMC)—*Cont.*
 multivariable formulation, 744–748
 predictive structure, 728
 single-variable formulation, 738
 tuning, 750
- Dynamics:
 dead time, 103, 140, 324, 328
 first-order systems, 57, 137, 323, 328
 integrating process, 140–141, 564–566,
 325, 328
 recycle systems, 155, 840
 second-order systems, 138–140, 324,
 328
 series systems, 143, 328
 staged systems, 157
 (*See also* Modelling procedure)
- ## E
- Economic value of control, 28–35
- Electrical circuit, 137, 138
- Emergency control systems, 20, 230–231,
 794–799
- Empirical modelling:
 dead time, 144, 179–181, 190
 diagnostics, 61, 183, 194
 experimental design for, 181, 188
 multivariable systems:
 open-loop, 197, 622
 partial closed-loop, 629, 670
 process reaction curve, 179
 signal-to-noise, 182
 six-step procedure, 176
 statistical method, 188
 use in control analysis, 280, 338–343
- Energy balance:
 in modelling, 53–54, 898
 strategy in distillation, 664
- Energy reduction, control systems for, 23,
 716–717, 791, 861–866
- Environmental protection, 21, 768, 797
- Equal-percentage characteristic, 521
- Equilibrium, ideal stage, 159
- Equilibrium, phase, 159, 538
- Error:
 measures of control performance, 219
 in sensor measurement, 383, 773
 variable used by controller:
 model predictive, 585, 741
 proportional-integral-derivative,
 242–243

- Euler:
 - identity, 934
 - numerical integration, 83
 - Evaporator, 676
 - Evolutionary operation, 871
 - Experimental modelling (*see* Empirical modelling)
 - Exponential filter:
 - analog, 390, 393
 - digital, 392, 988
 - predictive control, 593
 - principle, 389
 - External feedback, 399
 - External variable, 54,
- F
- Factor, partial fractions, 107, 931
 - Factorization, model, 590
 - Feasible region (*see* Operating window)
 - Feedback control:
 - block diagram for, 243, 463, 586, 630
 - components of loop, 212–213
 - compared with feedforward, 488
 - definition, 6
 - negative, 6
 - performance (*see* Control performance)
 - pluses and minuses, 229
 - positive, 142
 - selecting variables in, 216–218, 438, 536, 775, 779, 828
 - (*See also* PID; IMC; DMC)
 - Feedforward control:
 - algorithms for:
 - digital, 492–493
 - general derivation, 485
 - lead/lag, 485–486
 - transfer function, 488
 - block diagram for, 489
 - design criteria for, 487
 - goal, 484
 - digital implementation, 492
 - examples:
 - chemical reactor, 495
 - distillation, 501
 - fired heater, 499–500
 - heat exchanger, 497–498
 - feedback:
 - combined with, 486, 497
 - comparison with, 488
 - Feedforward control—*Cont.*
 - perfect, 484
 - performance guidelines:
 - dynamic behavior, 491
 - model error, 490
 - stability, effect on, 488, 502
 - tuning, 493
 - Fieldbus, 375
 - Filtering:
 - algorithms:
 - continuous, 390
 - discrete, 392, 988
 - aliasing in, 393
 - low-pass, 390
 - perfect, 390
 - performance, effect on, 391
 - reasons for, 389
 - z-transform, 979
 - Final control element, 5, 10, 212–213, 226, 438, 776–777
 - Final value theorem, 104, 979
 - Fine tuning, 289–293
 - Finite difference, 366–367, 493, 923
 - Fired heater:
 - cascade control, 494
 - feedforward, 522–524
 - industrial case study, 961–972
 - loop pairing, 694–695
 - outlet temperature control, 29
 - First-order system:
 - continuous, 137
 - discrete approximation, 922
 - dynamic behavior, 59, 137–138
 - Bode diagram, 323
 - example systems, 137
 - frequency response, 328
 - time-domain responses, 136
 - series of:
 - interacting, 145–148
 - noninteracting, 143–145
 - transfer function for, 144
 - Flash process:
 - alarms for, 795–796
 - control design for, 802
 - control objectives for, 20–25, 768–769
 - controllability of, 787–788
 - degrees of freedom, 787–788
 - dynamic response of, 803
 - inferential control of, 537–541
 - operating window, 788–789
 - safety control, 794–799

Flow:
 control, 13
 measurement, 387
 ratio, 499, 684
 value, 80

Forcing function, 895

Frequency distribution, 31–35

Frequency response, 121
 amplitude ratio, 121–122
 of basic systems, 323–326, 328
 Bode plot, 123
 closed-loop control performance,
 412–420
 computer program for, 317, 421
 direct evaluation, 122
 phase angle, 121, 123
 of series systems, 144, 316–317
 shortcut from transfer function, 122
 in stability analysis:
 Bode stability, 314–316
 transient, complete, 119–120

Furnace (*see* Fired heater)

G

Gain:
 controller:
 feedback, 245, 587
 feedforward, 485
 nonlinear, 567
 frequency dependent, 315
 margin, 338
 process, 87
 disturbance, 224
 feedback, 224, 254
 multivariable process, 627
 steady-state, 58

Gain scheduling, 518, 529

H

Heat exchanger:
 with bypass:
 feedback control, 784
 model, 76–80, 939–942
 numerator zero, 941
 recycle systems, 785
 transient response, 942

Heat exchanger—*Cont.*
 cascade, 458
 dynamic model, 76–80
 feedback control transient, 256
 feedforward, 486
 linearizing characteristic, 523–524
 refrigeration, 475, 884–885
 steam condensing, 777
 stirred tank, 76–80

Heaviside, 932

Hierarchy, 476, 826, 829

High signal select, 713

Histogram, 29–31

Hold:
 first order, 364
 zero-order, 364

Holdup time, 562

Horizon:
 input, 749
 output, 749

Hydrocracker control, 753

I

Identification (*see* Empirical modelling)

IMC (*see* Internal model control)

Impulse function, 101

Inferential control:
 block diagram, 537
 design criteria, 542
 design procedure, 543
 examples:
 chemical reactor, 549–552
 combustion, 552–554
 distillation, 545–549
 flash process, 537–541
 goal, 536
 multiple correlated measurements, 554

Initialization:
 controller, 245, 402
 filtering, 392

Input:
 terminology for control, 6
 terminology for modelling, 53
 typical time functions, 220–222

Input-output (*see* Cause-effect
 relationship)

Input processing:
 conversion, 212–213, 387
 filtering, 389

- Input processing—*Cont.*
 units, 388
 validity, 387
- Integral:
 Laplace transform of, 102
 numerical approximation, 366
 z-transform, 978
- Integral stabilizability, 692
- Integral error measures:
 IAE, integral of absolute value, 219
 IE, integral of error, 219, 677
 ISE, integral of squared, 219
 ITAE, integral of product of time and absolute, 219
- Integral mode:
 advantage/disadvantage, 249
 equation for explicit mode, 248
 implicit (*see* Model predictive control)
 tuning constant, 248
 (*See also* Anti-reset windup)
- Integral windup (*see* Anti-reset windup)
- Integrating factor, 58, 895
- Integrating process:
 dynamic behavior, 136
 general form, 140–141
 levels, 564
 stability, 307–308
 (*See also* Level control)
- Integrity, 637, 672, 692
- Interacting series, 145–148
- Interaction:
 block diagram, 624
 controllability, effect on, 627, 651
 (*See also* Decoupling)
 definition, 620
 integrity, effect on, 672–674, 692, 850
 measure of (*see* Relative gain array)
 modelling:
 empirical, 622
 fundamental, 621
 operating window, effect on, 624–626, 789
 performance, feedback control:
 loop pairing, 671–681
 tuning, 682–683
 stability, effect on, 638
 transfer function, 629–630
 tuning, 641–646
 (*See also* DMC)
- Internal model control (IMC):
 digital form, 595, 994
 filter for, 593
 model inverse, approximate, 590, 994
 performance, 597
- Internal model control (IMC)—*Cont.*
 structure, 592
 tuning:
 for IMC controller, 598
 for PID controller, 609
- Inventories:
 control of (*see* Level)
 models for, 564–565
 reasons for and against, 562–563
 sizing, 562, 572–574
- Inverse:
 approximate, 590
 exact model, 588, 729–730
 feedback as, 588
- Inverse Laplace transform, 99
- Inverse response:
 control performance, 430–431, 444, 996–1000
 multivariable systems, 669–671
 open-loop, 152–155, 943–946
- ISE (*see* Integral error measures)
- ITAE (*see* Integral error measures)
- J**
- Jacketed reactor, 476
- L**
- Lag (*see* First-order system)
- Laplace transform:
 applications:
 solving ODE, 102
 transfer function, 111
 of common functions, 100
 definition of, 98
 of derivatives, 101
 of integrals, 102
 partial fractions, 107, 931–935
 properties, 98–99
- Lead:
 lead/lag algorithm, 485–486, 595, 687, 923
 time constant, 152
- Least squares:
 as approximate inverse, 737
 assumptions in, 191

- Least squares—*Cont.*
 in design of dynamic matrix control, 737–738
 empirical modelling, 188–190
 solution of linear problem, 191
- Level:
 control of:
 linear PI, 566
 nonlinear PI, 567
 control objectives, averaging and tight, 563–564
 controller tuning, 568
 draining tank, 75–77
 inventory size, 572
 process model for:
 non-self-regulating, 140, 565
 self-regulating, 75–77
 sensors, 577
 series processes, 574–576
- Limit cycle, 906
- Linear operator, 70
- Linear programming, 866–868
- Linearity, definition of, 70
- Linearization, 71–72
 control loop, 517–529
 effect on stability analysis, 275, 284, 513–517
 Taylor's series, 71
- Load (*see* Disturbance)
- Long-time behavior, 109, 119–121, 306, 936–937
- Low-pass filter, 390
- Low signal select, 710–713
- Lumped-parameter model, 47, 53
- M**
- Manipulated variable, 207, 212, 218, 226, 243, 276
- Manual operation, 228
- Mass, conservation of, 53
- Master controller (*see* Cascade)
- Material, conservation of, 53
- Maximum deviation, 221
- Maximum overshoot, 220
- Measured variable:
 accuracy, 383 (*See also* Filtering)
 linearity, 387
 range, 383–384
 reproducibility, 383
 sensor dynamics, 212–216, 773
- MIMO (*see* Interaction, Multiloop control; Multivariable control)
- Mixing process, with dead time:
 control of, 270–277, 413–415
 model of, 271
- Mixing process, three-tank:
 adaptive tuning for, 517–519
 control of:
 derivative-only, 249–251
 integral-only, 248
 internal model, 595
 proportional-integral-derivative, 282–285, 330–332
 proportional-only, 245–248
 mismatch from true process:
 due to nonlinearity, 283–285, 512–517
 effect on control performance, 431–432
 effect on stability, 345–346
 model of:
 empirical, 186
 fundamental, 223–224
 input-output, 223
- Model predictive control (MPC):
 for cascade control, 606
 dead time, 606
 error, feedback, 585
 with feedforward control, 607
 filter for robustness, 592–593
 internal model control (IMC), 590
 perfect control, 587–588
 process inverse:
 approximate, 590
 exact, 587–588
 saturation of final element, 604
 Smith predictors, 600
 structure, 586
 transfer function, 592
 two-degree-of-freedom, 594
 zero-offset requirements, 587, 593, 601
 (*See also* DMC)
- Modelling procedure, 50
 approximate, 909
 empirical, 175
 fundamental, 53
 linearized, 71
- Moments:
 definition, 909
 for impulse response, 910
 use in correlations, 281, 286–287, 336, 598
 use in modelling, 912
- Monitoring, 23, 799

Move suppression factor, 743, 749

Multiloop control:

- block diagram for, 624, 630
- comparison with single-loop, 616
- control performance:
 - input forcing, 663–669
 - interaction, 628
 - interactive dynamics, 669–671
 - operating condition, 663
- controllability, 626, 651, 780–781
- decoupling:
 - lead/lag, 687
 - model sensitivity, 689
- loop pairing, 671
- relative disturbance gain (RDG), 677–681
- tuning, 646–649, 682
(*See also* Control design, Interaction)

Multivariable control:

- centralized:
 - model inverse for, 729, 738
 - structure, 728
- (*See also* Dynamic matrix control; Multiloop control)

N

Negative feedback, 6, 141–142, 207, 242

Niederlinski criterion, 692, 694–695

Noise:

- effect on tuning, 275–276, 292, 915–920
- frequency content, 423–425
- signal-to-noise ratio, 182
(*See also* Filtering)

Noninteracting series systems, 143

Nonlinear:

- control, 517, 520, 570
- process, effect on operating window, 625–626, 782, 789
- process, effect on performance, 283–285, 512
- saturation, 399–402, 604, 707, 717
(*See also* Linearization)

Normal distribution, 30

Numerical solution methods:

- for algebraic equations, 902–903
- for differential equations, 82–84

Numerical solution methods—*Cont.*

- frequency response, 317, 421
- for integrals, 366, 917

Nyquist, 314

O

Objective function, 271, 736, 743, 864, 866, 917

Objectives, control, 20, 268, 768, 838

Offset, steady-state:

- definition, 218, 240
- with feedback control, 246, 249, 251
- with feedforward control, 488
- integral mode, 249, 587
- level control, 571

On-off control:

- heating, 5, 230
- model, 67–69

One-way decoupling, 690

One-way interaction, 631, 636–637

Open-loop operation, 228

Open-loop transfer function:

- $G_{OL}(s)$, 316
- terminology, 328

Operability, 778

Operating window, 26–27, 226, 440, 625–626, 720–721, 789

Optimization:

- constraints, 868
- control methods for:
 - control design, 861
 - direct search, 870
 - model-based, 866
- in controller tuning:
 - control objectives, 268, 917
 - correlations from, 281, 284, 598
- plant economics:
 - effect of variance, 31, 33
 - profit contours, 31, 43

Order of system, 112

Ordinary differential equations, 47, 56, 102

Output:

- meaning for control, 6
- meaning for modelling, 53

Overdamped, 138–139

Overshoot, 219–220

P

- Packed bed:
 - cascade control, 471–473
 - empirical model, 202
 - feedforward control, 495–497
- Padé approximation, 913
- Pairing, loop, 671
- Partial control, 779, 827
- Partial fraction expansion, 107, 932–935, 980
- Performance, (*see* Control performance)
- Period of oscillation, 121, 222, 315, 330, 343
- Periodic behavior, 5, 67, 343, 906
- pH control, 527, 776
- Phase angle, 121–123
- Phase equilibrium:
 - in distillation, 159
 - in flash process, 538
 - K values for, 538
 - relative volatility, 159
- Phase margin, 340
- Physical realizability, 496, 588
- PI, PID (*see* Proportional-integral-derivative controller)
- Pneumatic:
 - control valve, 213
 - controller, 257
 - signal transmission, 212–213, 891
- Polar form:
 - complex numbers, 122, 316–318, 421
 - frequency response for series systems, 317
- Poles:
 - definition of, 113
 - effect of control on, 247, 254–256, 259, 313
 - effect on dynamic response, 109, 113, 310
 - effect of process design on, 141–142, 151, 155, 157, 425, 440, 564, 785, 902, 906
 - effect on stability, 109, 310
- Position (full) form of digital controller, 367
- Predictive control (*see* Model-predictive control)
- Primary controller (*see* Cascade control)
- Process dynamics:
 - effect on control performance, 415, 426, 438, 440, 663, 694
 - effect on stability, 334
 - effect of zeros, 152, 939
 - empirical modelling of, 196
 - fundamental modelling of, 53
 - linearized models, 74
 - recycle process structures, 155
 - series process structures, 152, 939
 - staged process structures, 157
- Process examples, guide, 925–929
- Process reaction curve, 179, 187
- Product quality, 23, 768
- Profit function (*see* Objective function)
- Proportional:
 - controller mode, 245
 - tuning constant, 245
- Proportional band, 398
- Proportional-integral-derivative (PID) controller:
 - in adaptive control, 517
 - in cascade control, 458, 468–469
 - derivative mode, 250
 - effect on offset, 251
 - effect on stability, 326
 - digital form of controller, 367–369
 - frequency response, of controller, 366–367
 - initialization, 245, 402
 - integral mode:
 - effect on dynamic response, 249
 - effect on offset, 249
 - effect on stability, 325, 336–337
 - windup, 399
 - mode selection, 436
 - output limits, 403
 - proportional mode:
 - effect of dynamic response, 245, 272
 - effect on offset, 245
 - effect on stability, 246
 - tuning:
 - Ciancone, 281, 286
 - IMC, 609
 - Lopez, 287
 - multiloop, 641–646
 - selection, 347
 - Ziegler-Nichols, 329, 347
- Proportional-only control, 245, 571
- Pulse, input function, 64, 101

Q

Quadratic dynamic matrix control, 751
 Quick-opening valve, 521

R

Ramp:
 input function, 93
 output response, 93
 Random variable, normal distribution, 30
 Ratio control:
 effect on stability, 519
 as feedforward, 499
 flow ratio, 499
 reset by feedback, 519, 684
 Reactor (*see* Chemical reactor)
 Realizable, 496, 588
 Real-time operating system, 360
 Real-time optimization (*see* Optimization)
 Reconstruction of signal, 362
 Recycle:
 advantages of, 155–157, 785
 alternative source/sink, 832
 control of systems with, 785, 832,
 845–846
 effect of dynamic response, 156–157
 effect on stability, 156
 Refrigeration, 475, 885
 Regression (*see* Least squares)
 Relative disturbance gain (RDG):
 integral error measure, 677
 loop pairing, 678–679
 tuning factor, 678
 Relative gain array (RGA):
 calculation, 634
 control integrity, 637, 672
 definition:
 dynamic, 637
 steady-state, 633–634
 interpretations, 636
 loop pairing, 672–674, 695
 properties, 633–636
 stability, 637
 Relative volatility, 159
 Reproducibility, sensor, 383, 773
 Reset (*see* Integral)
 Reset time, 398

Reset windup (*see* Anti-reset windup)
 Resonant frequency, 414
 Reverse-acting feedback, 396
 Ringing controller, 368, 992
 Rise time, 219
 Robustness:
 importance, 241, 512
 performance, 268–269, 919
 stability, 338, 345
 tuning, 268, 919
 Root locus, 312
 Runge-Kutta numerical integration, 83

S

Safety, 20–21
 alarms, 795
 basic process control, 794
 failure position of final elements, 386
 good practices, 797
 safety interlock system (SIS), 796
 safety valves, 797
 Sampling (*see* Digital control)
 Saturation of controller output, 398, 604,
 707, 717
 Second-order system, 138–139
 Secondary controller (*see* Cascade)
 Select, signal:
 degrees of freedom, 710
 design criteria, 715
 tuning, 714
 (*See also* Constraints, control)
 Selection of variables:
 controlled variables, 216, 773, 827–828
 manipulated variables, 216, 226, 438
 measured disturbances, 487
 secondary cascade, 461
 Self-regulation, 141
 Sense (*see* Controller sense switch)
 Sensor:
 accuracy, 383
 cost, 772–773
 dynamics, 215, 773
 flow, 387
 identification symbols, 889
 level, 892
 noise, 276, 389, 424, 879
 range or span, 383
 reliability, 387

- Sensor—*Cont.*
 reproducibility, 383, 773
 signal transmission, 890
 temperature, 388, 536
- Separable differential equation, 58, 895
- Set point, 218, 242–243, 458, 586
- Settling time, 220
- Shannon's sampling theorem, 362
- Signal:
 conversion, 212
 analog to digital (A/D), 359
 digital to analog (D/A), 359
 electronic to pneumatic, 212
 digital transmission, 373
 dynamics, 213
 electrical transmission, 212
 pneumatic transmission, 212
 ranges, 213
- Signal-to-noise, 182
- Signal select, 710
- Simulation:
 closed-loop system, 423, 916
 performance measures, 917
 process dynamics, 83–84
 (*See also* Digital control)
- Sine input:
 amplitude ratio, 121–123
 first order, 123
 flow attenuation, 572
 typical input forcing, 136
 (*See also* Frequency response)
- Single-input single-output (SISO) (*see*
 Single-loop control)
- Single-loop control, 5–6, 208, 218, 243
- SIS (*see* Safety)
- Slave controller, 460
- Smith predictor:
 system structure, 600
 tuning, 602
 zero offset, 601
 (*See also* Model predictive control)
- Snowball effect, 847
- Split range:
 degrees of freedom, 706
 design criteria, 709
 tuning, 708
 (*See also* Constraints, control)
- Spring and dashpot, 137–138
- Stability:
 analysis:
 Bode, 314–317
 complex plane plots (*see* Root locus)
- Stability—*Cont.*
 analysis—*Cont.*
 Nyquist, 314
 pole calculation, 308–313
 root locus, 312–313
 simulation, 248
 chemical reactor, 902–906
 definition, bounded input-output,
 303–304
 effect of controller tuning, 312
 effect of process dynamics, 334
 effect of sampling period, 367–370
 feedforward, 488
 of linearized system, 305–308
 margin, 338–340
 multiloop, 630, 638
- Staged systems (*see* Distillation)
- Standard deviation:
 of averages, 394
 of data set, 30
 from set point, 221, 466
- Statistical modelling, 189
- Statistical process control:
 capability index, 880–881
 goal of preventing disturbances, 876
 Shewart chart, 876
 specification limit, 881
- Steady state:
 error (offset), 240
 feedforward control, 488
 operating window, 625–626
- Steam heat exchanger:
 bypass, 784
 condensing, 777
- Steam system:
 boiler, 27, 862
 header, 862
 turbines, 885
- Steam trap, 777
- Step:
 input function, 58, 136–138, 162
 Laplace transform, 99
 test (*see* Process reaction curve)
- Stiffness, 84
- Stirred tank (CST):
 chemical reactor, 62, 72, 85, 438, 835,
 897
 heat exchanger, 76–80, 458, 486, 523,
 939–943
 mixer:
 one-tank, 52, 270, 415

Stirred tank (CST)—*Cont.*
 mixer—*Cont.*
 three-tank, 186, 223, 282, 422–424,
 512, 595–596
 series reactors, 64, 430, 943
 typical assumptions, 52, 899
 Stochastic control performance, 293, 424,
 879
 Superposition, 70
 Surge tank, 119, 562, 572
 System definition, 52
 Systems analysis, 135

T

Target, 585–586
 Taylor series approximation, 71
 Temperature control:
 distillation, 545
 fired heater, 26, 31, 473, 500, 552, 961
 flash drum, 21, 538, 802
 stirred tank, 252–523
 Three-mode controller (*see*
 Proportional-integral-derivative
 controller)
 Time constant:
 empirical estimation, 179–180
 relation to process, 74, 137, 271, 900,
 942, 944
 series of, 143–145
 Time delay (*see* Dead time)
 Thermocouple, 388, 526
 Thermowell, 940
 Transfer function:
 closed-loop, 244, 462, 488, 586,
 629–630
 controller, 252–253
 definition, 111, 118, 983
 disturbance process, 224, 415, 666
 feedback process, 224, 270–271, 622,
 666
 instrument, 213
 matrix of, 624
 poles of, 113, 255, 259, 312–313
 zeros of, 113, 152
 Transient (*see* Dynamics)
 Transmission interaction, 629
 Transportation delay, 103–104
 Tray, distillation, general balances, 159

Tuning, feedback controller:
 digital PID control, 370
 dynamic matrix control, 750
 effect of process on, 281, 334, 564–566,
 645
 internal model control, 598
 multiloop PID, 645, 682
 objectives (*see* Control, objectives)
 Smith predictor, 602
 stability margin:
 gain margin, 338
 phase margin, 340
 (*See also* Proportional-integral-
 derivative, tuning)
 Tuning, feedforward controller, 496

U

Ultimate controller gain, 330, 993
 Ultimate period, 330
 Underdamped process, 85, 138–139,
 253–256, 899–903
 Unstable systems:
 closed-loop system, 308–317
 process without control, 307–308,
 899–907
 Unsteady-state (*see* Dynamics)
 Utility systems:
 fuel gas system, 501, 810–811
 hot oil, 885
 steam system, 862
 (*See also* Refrigeration)

V

Validation, model, 60–61
 Valve:
 automated control:
 capacity, 217, 226, 385, 438–441,
 625–626
 characteristic, 520
 dynamic response, 213
 failure position, 386
 pneumatic power, 212–213
 range, 385
 manual, 228, 892
 positioner, 474

Valve—*Cont.*
 safety relief, 797
 stem, 81, 213, 474, 520
Valve position controller, 718
Variable:
 continuous, 98
 dependent, 56, 254
 deviation, 71, 111
 discrete, 188–189, 365, 973
 external, 56, 254
 manipulated, 5, 208, 213, 217
Variable structure:
 constraint control, 715
 multiple controllers, 716
 signal select, 710
 split range, 706
 valve position control, 718
Variance:
 definition, 30
 measure of performance, 221–222
Velocity form, controller, 367

W

Weir, 159
Wild stream, 499, 684
Windup, reset (*see* Anti–reset windup)

Z

z-transform, 973–975
 table, 975
Zero, sensor signal, 388
Zero-order hold, 364, 985
Zeros of transfer function:
 cancellation of pole and zero, 113
 effect on dynamic response, 152, 943
 effect on stability, 113
Ziegler-Nichols:
 closed-loop tuning, 329, 342–343
 open-loop tuning, 347
 process reaction curve, 179–180